


1000 Base-T Single port LAN Transformer Module

MODEL NO:GT2406D



Feature :

Designed to meet IEEE802.3at requirement

Wave solder conditions:Maximum temperature is $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$ time is 5~6sec(refer to SONY ss-00254-4 standard)

Suitable for End-span POE applications with 720 mA current capability.

Primary inductance(Lp):350uH Min (100KHz,100mV,8mA)

Storage Temperature range: -25°C To $+125^{\circ}\text{C}$




HI-POT:1500Vrms 1mA

Electrical Specifications at 25°C — Operating Temprange: 0°C To $+70^{\circ}\text{C}$

Part Number	Transformer Turns ratio ($\pm 5\%$) Receive Transmit	Insertion Loss (dB TYP) 1-100MHz	Crosstalk (dB TYP) 0.3~30 /60~100(MHz)	Return loss (dB TYP) 0.5-30/40/50/60-80(MHz)	CMRR (dB TYP) 0.1~100(MHz)
GT2406D	1:1 1CT:1CT	-1.0	-42 -33	-18/ -15/ -13.1/ -12	-30

Dimension: mm

Schematics:



Data sheet subject to change without notice

Unless otherwise specified, all tolerance are $\pm 0.25\text{mm}$

TE-JIN TECHNOLOGY CO.,LTD

TEL:86-769-81802907

FAX:86-769-81803750

E-mail:gc@tejinwwl.com

ADD: B1-2F,TangHong Industrial Zone ,Shi Jie Town, Dong Guan City, Guang Dong Province,China