


1000 Base-T Dual port LAN Transformer Module MODEL NO:GT4802D






Feature :

Designed to meet IEEE802.3ab requirement
Wave solder conditions: Maximum temperature is $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$
time is 5~6sec(refer to SONY ss-00254-4 standard)
Primary inductance(L_p):350uH Min. 100KHz, 100mV, 8mAdc
Operate Temperature: 0 to $+70^{\circ}\text{C}$
Storage Temprange: -25°C To $+125^{\circ}\text{C}$
HI-POT:1500Vrms 1mA


Electrical Specifications at 25°C — Operating Temprange: 0°C To $+70^{\circ}\text{C}$

Part Number	Transformer Turns ratio ($\pm 5\%$) Receive Transmit	Insertion Loss (dB TYP) 1-100MHz	Crosstalk (dB TYP) 0.1~ 100(MHz)	Return loss (dB TYP) 0.5-30/40/50/60-80(MHz)	CMRR (dB TYP) 0.1~100(MHz)
GT4802D	1CT:1CT	-1.4	-38	-16/-14.4/-13.1/-12	-40


Dimension: mm



PCB Layout mounting Hole (Top View):



Schematics:



Data sheet subject to change without notice

Unless otherwise specified, all tolerance are $\pm 0.25\text{mm}$

TE-JIN TECHNOLOGY CO.,LTD

TEL:86-769-81802907

FAX:86-769-81803750

E-mail:gc@tejinww.com

ADD: B1-2F,TangHong Industrial Zone ,Shi Jie Town, Dong Guan City, Guang Dong Province,China