

LAN COMPONENTS

2.5G Base-T Single port LAN Transformer Module

Model No: QT2401S



Feature :

Meets all IEEE802.3 and ANSI X3.263 Standards for 2.5G Base-T
SMD Environmental: Designed to meet IR 260°C peak.

Primary Inductance (L_p): 150uH Min. 100KHz ,100mV ,8mA_{dc}

Storage Temperature: -25°C to +125°C



Isolation: 1500Vrms 1mA

Electrical Specifications at 25°C — Operating Temperature Range: 0°C To +70°C

Part Number	Transformer Turns ratio ±3%	Insertion Loss 1-125MHz dB Max.	Return Loss 1-40 / 40-125MHz dB Min.	Cross Talk 1-125MHz dB Min.	DCMR 1-125MHz dB Min.
QT2401S	1CT:1CT	-1.0	-20 / -20+15*log(f/40)	-30	-30

Dimension: mm

Schematics:



Data sheet subject to change without notice

Unless otherwise specified, all tolerance are ±0.25mm

TE-JIN TECHNOLOGY CO.,LTD

TEL:86-769-81802907

FAX:86-769-81803750

E-mail:gc@tejinww.com

ADD: B1-2F,TangHong Industrial Zone ,Shi Jie Town, Dong Guan City, Guang Dong Province,China