


RJ45 1x1 Connector


Model No: RJ11DN101L00


Dimension: mm











Notes:

MECHANICAL

- Contact Material: Housing: Thermoplastic, Cool Gray 3U, UL94V-0
 - Housing: Thermoplastic, Cool Gray 3U, UL94V-0 Contact: Phosphor Bronze, area G/F gold plating.
- 2. RJ45 Cavities Conform to FCC and Part 68.
- 3. Operation Life: 750 cycles
- 4. Mating / Un-mating Force: 20N Max.
- 5. Retention Strength: 50N for 60 Secs.
- 6. Part recommend for wave soldering process with 260°C and 10 Secs. Max.

ELECTRICAL

- 1. Voltage Rating: 125Vac RMS
- 2. Current Rating: 1.5AMP
- 3. Contact Resistance: 50 milliohm Max.
- Insulation Resistance: 500 megohm Min. @500Vdc
- 5. Operating Temperature T= -40 $^{\circ}$ C to +85 $^{\circ}$ C
- 6. Storage Temperature T= -40 $^{\circ}$ C to +85 $^{\circ}$ C

Data sheet subject to change without notice.

Unless otherwise specified, all tolerance are ± 0.25 mm

TE-JIN TECHNOLOGY CO .,LTD

TEL:86-769-81802907 FAX:86-769-81803750 E-mail:gc@tejinww.com ADD: B1-2F,TangHong Industrial Zone ,Shi Jie Town, Dong Guan City, Guang Dong Province,China