


LAN COMPONENTS

10/100 Base-TX Dual Port LAN Transformer Module MODEL NO:TE1603D



Feature:





Designed to meet IEEE802.3 requirement
Wave solder conditions:Maximum temperature is $260^{\circ}\text{C} \pm 3^{\circ}\text{C}$
time is 5~6sec(refer to SONY ss-00254-4 standard)
Primary inductance(L_p): $350 \mu\text{H}$ Min (100KHz ,100mV ,8mA)
Storage Temprange: -25°C To $+125^{\circ}\text{C}$
HI-POT:1500VAC 1mA 1Sec

Electrical Specifications at 25°C — Operating Temprange: 0°C To $+70^{\circ}\text{C}$

Part Number	Transformer Turns ratio ($\pm 5\%$) Receive Transmit	Insertion Loss (dB TYP) 1-100MHz	Crosstalk (dB TYP) 0.3~100(MHz)	Return loss (dB TYP) 1~30/60/80(MHz)	CMRR (dB TYP) 0.3~100(MHz)
TE1603D	1:1 1CT:1CT	-1.0	-35	-16/ -12/ -10	-30

Dimension: mm

Schematics:



PIN2,6,8,9,11,15 CUT OFF

Data sheet subject to change without notice

Unless otherwise specified,all tolerance are $\pm 0.25\text{mm}$

TE-JIN TECHNOLOGY CO.,LTD

TEL:86-769-81802907

FAX:86-769-81803750

E-mail:gc@tejinww.com

ADD: B1-2F,TangHong Industrial Zone ,Shi Jie Town, Dong Guan City, Guang Dong Province,China