


10/100 Base-TX Dual Port LAN Transformer Module MODEL NO:TE2001D



Feature :

Designed to meet IEEE802.3ab requirement

Wave solder conditions: Maximum temperature is $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$
time is 5~6sec(refer to SONY ss-00254-4 standard)

Primary inductance(Lp):350uH Min. 100KHz, 100mV, 8mAdc

Operate Temperature: 0 to 70°C

Storage Temprange:- 25°C To $+125^{\circ}\text{C}$





HI-POT:1500VAC 1mA 1Sec

Electrical Specifications at 25°C — Operating Temprange: 0°C To $+70^{\circ}\text{C}$

Part Number	Transformer Turns ratio ($\pm 5\%$) Receive Transmit	Insertion Loss (dB TYP) 1-100MHz	Crosstalk (dB TYP) 0.3~100(MHz)	Return loss (dB TYP) 0.5~30/40/50/60~80(MHz)	CMRR (dB TYP) 0.3~100(MHz)
TE2001D	1CT:1CT	-1.0	-35	-18/ -15/ -13/ -12	-30

Dimension: mm

Schematics:



Data sheet subject to change without notice

Unless otherwise specified, all tolerance are $\pm 0.25\text{mm}$

TE-JIN TECHNOLOGY CO.,LTD

TEL:86-769-81802907

FAX:86-769-81803750

E-mail:gc@tejinww.com

ADD: B1-2F,TangHong Industrial Zone ,Shi Jie Town, Dong Guan City, Guang Dong Province,China